

4CH H.265 / 4 IN 1 HD Recorder / 5MP-H Recording



FEATURES

- 4 Ch With 4 Audio, 5MP-H Realtime Live View
- Support TVI 2.0, AHD 2.0, CVBS, IPCAM, CVI
- Support H.264 / H.265 video compression
- Support TVI / AHD / CVI / CVBS / IP video input
- Max. 600m for 5MP & 800m for 720p AHD signal
- Remote view : Support free P2P, Android / iOS / PC



Plug &
Play



LAN
Port



Audio
Support



HDMI
Out Put



USB
Interface



iOS &
Android



Cloud
Recording

Technical Specifications

Product Code	T38153
Processor	Embedded Linux
Operating System	H.264 / H.265
Video Compression	Support, Max 4ch AHD @ 5MP-H / 4MP-H / 3MP-H / 1080P / 960P / 720P;
DVR Mode	TVI @ 5MP-H / 4MP-H / 3MP-H / 080P / 960P / 720P; CVI @ 1080P / 720P; Analog video real time input
Mixed Mode	Support, Max 4CH
Video Input Format	TVI 2.0 : 720P @ 25 / 30 / 50 / 60fps, 1080P @ 25 / 30fps, 3MP - H@15 / 25 / 30fps, 4MP-H @ 15 / 25 / 30fps, 5MP - H@15 / 25 / 30fps, AHD : 720P @ 25 / 30fps, 1080P @ 25 / 30fps, 3MP-H @ 12fps 4MP - H@15 / 25 / 30fps, 5MP - H@ 12 / 20fps CVI : 720P @ 25 / 30fps, 1080P @ 25 / 30fps, CVBS : (@ PAL 960H / NTSC)
Video Encoding Resolution	5MP - H (1280 x 1952) @ 12fps, 4MP - H (1280 x 1440) @ 15fps 3MP - H (960 x 1536) @ 12fps 1080P / 1080P - H (960 x 1080) @ 15fps 720P / 960H / D1@25 fps
Video Encoding Rate	512 Kbps -- 6Mbps
UTC	Support 4ch
Audio Input	Support 1RCA (4ch Coaxial Audio Support)

HDMI Output	1 CH HDMI Interface; Max Resolution : 1920 x 1080 / 60Hz	
VGA Output	1 CH VGA Interface; Max Resolution : 1920 x 1080 / 60Hz	
Audio Output	RCA Audio output x 1, HDMI Audio output	
Stream Type	Audio and video flow mixing flow/video stream	
Audio Compression	G.711	
Playback	2CH; 5MP-H Playback	
Recording Mode	Manual, Schelude (Reguler / Continuous), MD, Alarm, Stop	
Search Mode	Time / Date, Alarm, MD &Exact Search (accurate & Second), Smart Search	
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, Buzzer,	
	Snapshot Snapshot On Email	
Device Control	Remote Control & Mouse	
Soft Power-Off	Support	
Storage Type	1 x SATA Interface	
Storage Capacity	6TB In Max	
Backup	USB Backup & Internet Backup	
Network Interface	RJ45 10M / 100M Internet Interface	
USB Interface	2 x USB 2.0 Interface	
Power	DC +12 V / 2A	
Power Consumption	≤10W	
Temperature	– 10°C — 50°C	
Working Humidity	10% – 90%	
Dimension	43 x 204 x 254 (H x W x L)	
Weight Net	0.710KG	
Weight Gross	1.120KG	

*** Note: Product specifications are subject to change without prior notice.**