



## Features

- ◆ IP PTZ 5 Megapixel.
- ◆ Support P2P viewing.
- ◆ 9 pcs Array 42Mil Led+2PCS Laser Led,IR range up to 150M.
- ◆ ONVIF2.4 ; Compatible with HIKVISION, DAHUA, XM, CP Plus . etc
- ◆ Compatible with CMS,UC2, Milestone and AXXON platform. etc
- ◆ Intelligent IR illumination & power consumption is variable.

Product code	T17819-BB
Chipset	GK7205V300 + SONY335
Image Sensor	1/3 SONY335 CMOS Sensor
Resolution	5MP 2560*1920
Output Pixel	2592x1944@15fps,2592x1520@22fps
video compression	H.264/H.265
Lens	F=4.35mm~96.3mm
IR LED	6 Array LED Array + 2 Laser LED
Min.illumination	Color:0.5Lux B/W:0.05Lux IR ON:0Lux
IR Range	150 Meters
Zoom	20X Optical + 16Digital Zoom
WDR	Support DWDR
Day & Night	Auto OR Manual; Color / BW/AGC
Noise Reduction	3D NR
S/N Ratio	≥50dB
Rotation Range	Pan:0~360°, Tilt:0~93°
Rotation Speed	Pan:0~80°/s, Tilt:0~40°/s
Auto Flip	Horizontal 180°,Vertical 93°
Preset Points	220pcs presets ( dwell time 01-60s interval available)
Preset Speed	1-64 grades available
360° Scan	1-64 grades setting available
AB scan	User programmabel (scan speed 1-64)
Tour	3 groups ( each group 16 preset, dwell time and speed selectable)
PWR On Action	Memory/Pattern 1/Tour 1/360° scan/A-B scan/Park 1/None
Park Mode	Tour 1/360° scan/A-B scan/Park 1/None
Park Time	1-60mins setting available
P2P	Support, Android/Iphone/Windows Pc
Protocol	TCP/IP,HTTP,NTP,IGMP,DHCP,UDP,SMTP,RTP,RTSP, ARP,DDNS,DNS,PPPoE,P2P,
Compatibility	HIKVISION ,DAHUA, XM NVR , Milestone and AXXON platform,Juan
Power	DC12V 4A
Connectors	RJ45
Temperature	Indoor: 0°~ +40°, Outdoor: -40°~ +60°
Storage Temperature/Humidity	≤95% Non Condensing
Dimension	W265mm*H317.98mm
Lightning Protection	Transient voltage 6000V
Housing type	Metal (IP66)
Weight Net	2.95KG
Weight Gross	4.5KG

Technical Data Sheet

