

4K Auto Tracking Camera (TV-VCCAM4KAUTFRM) T29961-A



FEATURES

- Adopt the most advanced image DSP.
- Sony 1/2.8" 8MP sensor.
- High quality 8MP optical full glass lens.
- Ultra-high definition and crisp image.
- Support max 3840 x 2160 @30 UHD resolution.
- 4x digital zoom.
- 120 degree view angle without distortion.
- Power via USB, a single USB2.0 cable for video output, camera control and power supply directly, friendly-use and flexible operation.
- Fast video switch : only 1 second
- Unique and patent camera housing and mechanism design.
- built-in dual microphone, pick up distance 5meters
- Electronic pan/tilt design, no mechanism problem
- Support WDR, 3D noise reduction
- Support image flip function, camera can be installed upside down



WDR



Plug & Play



Ultra HD Video



4X Zoom



8MP Sensor



120° Ultra-wide View

Technical Specification

| | |
|-----------------------|--|
| Sensor | 1/2.8 inch high quality 8MP CMOS sensor |
| Video Format | YUY2/NV12 : 1920 x 1080 @30, 1280 x 720 @30, 640 x 480 @30, 320 x 240 @30. MJPG/H.264/H.265 : 3840 x 2160 @30, 2560 x 1440 @30, 1920 x 1080 @30, 1280 x 720 @30, 640 x 480 @30, 320 x 240 @30. |
| Digital Zoom | 4x lossless digital zoom |
| Horizontal View Angle | 120° |
| F.no | 2 |
| Focal Distance | f = 2.22mm |
| Control Interface | USB2.0 (UVC) |
| Noise Reduction | 3D |
| Minimum Lux | 0.1 lux |
| White Balance | Auto / Manual / Auto Tracking / One Push / Indoor / Outdoor / Sodium Lamp / Fluorescent Lamp |
| Anti-Flicker | OFF / 50Hz / 60Hz |
| Gamma | Support |
| In-Ceiling Mount | Support |
| Mirror | Support |
| Iris | Fixed |
| Electronic Shutter | Auto / Manual |
| BLC | Support |

| | |
|---------------|----------------------------------|
| Image Flip | Support |
| USB Power | Support |
| Input Voltage | 5V 1A |
| Dimension | 199mm (W) x 93mm (H) x 65 mm (D) |
| Weight | NW: 0.319 Kg, GW: 0.856 Kg |
| Accessories | Remote, Touch Cable. |

*** Note: Product specifications are subject to change without prior notice.**