

Smart 4G Linkage Pan-Tilt Camera



FEATURES

- 2+2MP 4G Smart Linkage Pan-Tilt Camera
- 4MM+8MM Fixed Lens
- PT Horizontal & Vertical Movement Range Pan 266°, Tilt 90°
- Dual monitoring. One camera for Wide angle monitoring, One camera for PT detailed monitoring.
- Built-in high-sensitivity Mic and Speaker For Half Duplex Audio Intercom
- Support 10X Digital Zoom
- Can be set 6 preset points favorite locations
- Unique Three Smart Night Vision Modes
- Micro SD Card Up to 256GB & Cloud Storage (Optional)
- 4G Connection, QR code camera configuration with mobile/PC
- Active defense Siren & Lights
- Customize Voice Recordable message for Audio Alerts Broadcast
- Area motion detection, Humanoid detection, Push Realtime Notification on the Application
- Support monitoring : PC / Mobile on TrueCloud
- Compression : H.264/H.265/H.265+
- Alexa Support



4G SIM Support



256GB SD Card



2+2 MP Resolution



Auto Human Tracking



Onvif Support



Works with Alexa



Two Way Audio Intercom



Cloud Recording

Technical Specifications

Product Code	T18178-AE
Image Sensor	1/2.9" 2MP+2MP HD CMOS Dual Sensor
Resolution	1920 X 2160
Lens	Bullet : 4mm fixed lens PT Dome : 8mm fixed lens
IR LEDs	Bullet : 6 Pcs PT Dome : 12 Pcs
Infrared IR Distance	>30 Meters
White LEDs	Bullet : 6 Pcs PT Dome : 12 Pcs
Infrared IR distance	>20 Meters
Minimum Illumination	Color : 0.001 Lux, BW : 0 Lux
Day & Night Mode	IR / Smart / Full Color
S/N Ratio	> 39.1 dB
White Balance	Auto
3D-DNR	Auto
Mirror/Flip	On / Off
Video Streaming	Mainstream : 1920 x 2160 Substream : 800x896
AI Features	Human Detection Motion Detection
Privacy Mode	Support 4 Zone
Audio Streaming	AAC / G711A

Audio IN	Built in MIC
Audio OUT	Built in Speaker
Button	Device Reset button
TF /SD Card	Support Max 256GB
Protocol	N1 Protocol
Slots	Nano SIM Card Slot & Micro SD Card Slot
Connection Mode	4G Network
Light Mode	LED Flash; 4G Network not Connected LED Continue ON; 4G Network Connected
Power Input	DC Input 5V – 1A [C-type Connector]
Thunder Prevention	Standard IEC61000-4-5
Power Consumption	≤15W
Operation Temperature/Humidity	-10°C to +50°C / 30% to 80% RH
Storage Temperature/Humidity	-20°C to +60°C / 20% to 90% RH
Dimension	182 x 142 x 239mm(L×W×H)
Housing Type	Plastic Housing
Weight Net	0.586Kg
Weight Gross	0.808Kg

Similar Products



Smart 3MP 4G
Cube Camera



Smart 3MP 4G
Bullet Camera



Smart 3MP 4G
Dome Camera



Smart 3MP 4G
Robot Camera



Smart 3MP 4G
Mini PT Camera



4G PTZ
Camera

* Note: Product specifications are subject to change without prior notice.