

4G Mini PT Solar Linkage Camera



FEATURES

- 3+3MP 4G Mini PT Solar Linkage Camera
- 4MM+4MM Fixed Lens
- PT Horizontal & Vertical Movement Range Pan 266°, Tilt 90°
- Dual monitoring. One camera for Fixed monitoring, One camera for PT detailed monitoring.
- Built-in high-sensitivity Mic and Speaker For Full Duplex Audio Intercom
- Support 10X Digital Zoom
- Can be set 6 preset points favourite locations
- Unique Full Color & IR Night Vision Modes
- Micro SD Card Up to 256GB & Cloud Storage (Optional)
- 4G Connection, QR code camera configuration with mobile/PC
- Active defence Siren & Lights
- Built-in Battery 18000 mAh rechargeable lithium battery with 7 Watt Solar Panel
- Built-in PIR Sensor
- Customise Voice Recordable message for Audio Alerts Broadcast
- Area motion detection, Humanoid detection, Push Realtime Notification on the Application
- Support monitoring : Pc / Mobile on Truecloud
- Compression : H.264/H.265



4G SIM Support



256GB SD Card



3+3MP Resolution



Battery Backup



Auto Human Tracking



IP66 Rating



High Quality Solar Panel



Cloud Recording



Location Presets

Technical Specifications

Image Sensor	1/2.8" 3MP+3MP HD CMOS Dual Sensor
Resolution	2304 x 2592
Lens	Bullet: 4mm fixed lens PT Dome: 4mm fixed lens
IR LEDs	Bullet : 4 Pcs PT Dome : 4 Pcs
Infrared IR Distance	>30 Meters
White LEDs	Bullet : 4 Pcs PT Dome: 4 Pcs
White LEDs Distance	>20 Meters
Minimum Illumination	Color : 0.001 Lux, BW : 0 Lux
Day & Night Mode	IR / Full Color
S/N Ratio	> 39.1 dB
White Balance	Auto
3D-DNR	Auto
Mirror/Flip	On / Off
Video Streaming	Mainstream : 2304 x 2592@15fps Substream : 800 x 896@15fps
AI Features	Human Detection Motion Detection Human Tracking
Audio Streaming	AAC/G711A
Audio IN	Built in MIC

Audio OUT	Built in Speaker
TF /SD Card	Support Max 256GB
Slots	Nano Sim Card Slot & Micro SD Card Slot
Battery	Built-in 18000mAh Rechargeable battery
Solar Panel	7 Watt
PIR Detection	10 meters distance, 120 degrees cover
Connection Mode	4G Network
Light Mode	LED Flash; 4G Network not Connected
	LED Continue ON; 4G Network Connected
Power Input	DC Input 5V – 2A [C-type Connector]
Thunder Prevention	Standard IEC61000-4-5
Power Consumption	≤15W
Operation Temperature/Humidity	-10°C to +50°C / 30% to 80% RH
Storage Temperature/Humidity	-20°C to +60°C / 20% to 90% RH
Dimension	185 x155 x 210mm (L×W×H)
Housing Type	Plastic Housing
Weight Net	0.900Kg
Weight Gross	1.8Kg

Similar Products



4MP 4G Solar With
Battery Bullet Camera



Solar Panel
12Ah



3MP 4G Dual Lens
Mini PT Camera



3MP 4G Dual Lens
Linkage PT Camera



3MP 4G Mini PT
Camera



3MP 4G
PTZ Camera

* Note: Product specifications are subject to change without prior notice.