

TrueBoard 278.13cm (110 inch) 8GB/128GB Built-in-Camera



FEATURES

- Ultra Resolution Output.
- Zero bonding technology for natural writing experience.
- Front audio stereophonic speakers.
- Industrial grade aluminium frame.
- Multiple signal input HDMI, SPDIF, RS232, AV I/O, Earphone.
- Infrared touch technology for rich writing experience.
- Password Lock protected.
- 400cd/m² ±10% high brightness.
- Built in Android OS with optional windows OS.
- 4mm protect and anti-scratch glass.
- 20 Point Touch. ≤5ms response.



Zero Bonding Technology



Type-C Port



2 x 20W Speakers



400 nits Brightness



Screen Recorder



9H Toughened Glass



60000* Hours Screen Life



Anti Glare Screen



Bluetooth Connectivity



1 mm Writing Height



4K UHD Resolution



App & Tool Lock Feature



Reverse Screen Mirroring

TECHNICAL SPECIFICATION

Model No.

T291125-A

DISPLAY


Diagonal Size	278.13cm (110 inch)
Bonding Technology	Zero Bonding
Display Orientation	Landscape
Screen Type	TFT LCD(Direct-LED Backlight)
Aspect Ratio	16:9
Pixel Pitch	0.9987 (H) X 0.9987 (W)
Response	≤8ms
Resolution	3840 x 2160 pixels
Contrast Ratio	5000:1 Dynamic, 1200:1 Static
Brightness(cd/m ²)	400cd/m ² ±10%
Display Area	2438mm(H) x 1372mm(V) (96 x 54 in)
Color	16.7 million colors
View Angle	H:178° V:178°
LED Lifespan	60,000* hours

System

OS	Android 14
CPU	Quad Core Cortex-A37, 1.4 GHz
Chipset	Pro-9679
GPU	Mali-G52 MP2 (2EE)
RAM	8GB
Storage	128GB
OSD Language	English, Hindi, Gujarati, Telugu
Video Format	PAL, NTSC
Optimum Resolution	3840 x 2160 pixels @ 60 HZ


Video / Picture Decoding	– AVS2 MP-10@L8.2, 4Kx2K@60fps – ITU-T H.265 Main 10 Profile@Level 5.1 High-tier, 4Kx2K@60fps – VP9 Profile 2 10-bit, 4Kx2K@60fps – SHVC, ATSC 3.0 (For H.265) – FHD HFR (For H.265) – H.264 AVC HP@L5.1 up to 4Kx2K@30fps – H.264 MVC up to 1080P@60fps – MPEG-1 MP/HL up to 1080P@60fps (ISO-11172) – MPEG-2 SP@ML, MP@HL, up to 1080P@60fps (ISO-13818) – SuperClear, smooth edge – Support 3D detection – Support 2D to 3D – Support 0D/1D/2D Local Dimming – Support Ambi-Light – Support video rotation – AVS2 MP up to 4Kx2K@60fps – MPEG-4 ASP@L5 up to 1080P@60fps (ISO-14496) – WMV/VC-1 SP/MP/AP up to 1080P@60fps – AVS-P16 (AVS+) / AVS-P2 JiZhun Profile up to 1080P@60fps – Multiple language and multiple format sub-title video support – MJPEG and JPEG unlimited pixel resolution decoding (ISO/IEC-10918) – Supports JPEG thumbnail, scaling, rotation and transition effects – Supports *.mkv, *.wmv, *.mpg, *.mpeg, *.dat, *.avi, *.mov, *.iso, *.mp4 and *.jpg file formats
Picture / Video Encoding	– Independent JPEG and H.264 encoder with configurable performance/bit-rate – JPEG image encoding – H.264 video encoding up to 1080P@30fps with low latency
Support Resolution	3840x2160, 1920x1080, 1680x1050, 1600x1200, 1440x1050, 1360x768, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 4K
I/O Port	
Rear Input	HDMI 2.0 x 2, USB 3.0 x 1, USB 2.0 x 2, SPDIF x 1, RS232 x 1, Touch USB x 1, RJ45
Front Input	Line in/Mic in (3.5mm) x 1, Line Out/Earphone (3.5mm) x 1.
	USB 3.0 x 3 (Both work on Android and OPS),
	HDMI 2.0 x 1, Touch USB x 1, Type-C x 1, Light Sensor x 1
Media Format	
Audio	MP3, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP
Video	H.264, VP8, RV, WMV, AVS, H.263, MPEG4
Picture	JPG, BMP, PNG
Touch Features	
Touch Type	Infra-red Touch, 20 Point Touch (Android), 40 Points (Windows)
Glass Hardness	9H (Pencil), 7 (Mohs)
Glass Type	4mm Mohs, Heat Tempered Glass, Explosion Proof, Anti Glare, etc
Response Time	≤5ms
Touch Object	All Opaque objects, such as Finger, Stylus Pen etc.
Touch Resolution	32768 x 32768 pixels

Touch Accuracy	1mm
Tracking Rate	4m/s
Scan Rate	200Hz
MTF	60million touch by each points
Minimum Touch Object	≥1MM
Essential Apps	Including Whiteboard, Annotate, Timer, Calculator, Split Screen, Record, Spinner, Screen Capture, Screen Record, Screen Share, Browser, PDF reader, Media Player, Screen Cast, etc.
Audio	
Speaker	2 x 20W
MICROPHONE	
Microphone Type	Linear array microphone
Microphone Quantity	8
Noise Ratio	67db
Sensitivity	-26 ± 1db
Pickup Voice Distance	≤10meters
Sampling Rate	16KHz
Features	Echo Cancellation
	Environmental noise suppression
	Sound source localization
	Sound Source tracking
	Reverberation removal
	Support for automatic gain
CAMERA	
Optical Lens Size	1/3.06" COMS Sensor
Resolution	48 Mega pixel (8000 x 6000 / 4160 x 3120 / 3840 x 2160 / 2560 x 1440 / 1920 x 1080 / 1280 x 720 / 1024 x 576 / 960 x 540 / 640 x 360)
Pixel Dot	1.12um x 1.12um
Video Compressed Format	MJPG/YUV/H.264/H.265
3D Noise Reduction	Support multi-level noise reduction
Shutter Type	Electronic Rolling shutter
Noise Ratio	≥39dB
Dynamic Range	≥45dB
Maximum Frame Rate	30FPS
View Angel	D: 117°
Distort	≤6%
AEC/Gain/White Balance	Auto
Video Format	2160P, 1920P, 1080P, 720P, 480P etc.
Lens	2.8mm Fixed
Communication Type	UVC



AI Features		
AI Gesture	Closely Place your plam in front of the camera to turn on or off the Voice & Body Tracking AI Camera	
Note	Camera Resolution 13 Megapixel Shows In Android & Windows 48 Megapixel Max.	
Panel Management		
OTA	Yes	
DMS (Device Management System)	• Display Product information (Like Location, IP,MAC, Operation System version, Specification etc.) • User management • Device management(Power on/off, Screen Lock, Sent Message, Program work flow, • Running log • Group management	
Own APK Store Market	Manage private APK store market	
Physical Specifications		
Handel	4	
Panel Net Weight (Kg)	86 KG	
Packed Weight (Kg)	98 KG	
Panel Dimensions	2500mm x 1464.1mm x 91.4mm (W x H x D) (without Wall Mounting Bracket or Floor Stand	
Packed Dimensions	2680mm x245mm x 1690mm	
VESA Mount Point mm	1000 x 800	
Power		
Power Requirements	AC 100 ~ 240V AC, 60/50Hz	
Energy Star Power Consumption	Normal 750W	
Power Consumptions (standby)	0.5W	
Ultra-Quiet Fanless Design	Yes	
Environmental		
Operating Temperature	0°C to 40°C(32°F to 104°F)	
Storage Temperature	-15° to 55°C(-5°F to 131°F)	
Operating Humidity	20% to 80% non-condensing humidity	
Storage Humidity	20% to 90% non-condensing humidity	
Packed Contents		
Kit	1 x AiO ADPM , 1 x Remote Controller, 1 x Wall Mount Bracket, 2 x Stylus, 1 x Power Cable.	
Other		
Option	Floor Stand Bracket	
Certification	BIS, CE, FCC, RoHS	

Dimension



(Unit:mm)

Additional Accessories (Optional)

OPS ADPM

CPU	Option : Core i5 / Core i7
RAM	Option : 4GB, 8GB, 16GB
Hard Disk	SSD 128GB~2TB or HDD 500GB~4TB

* Note: Product specifications are subject to change without prior notice.