

3MP Wi-Fi Mini PT All-Time Color Camera



FEATURES

- 3MP (2304 x 1296) Resolution
- All-Time Color Vision
- Full Duplex Audio Intercom (Built-in High Sensitivity Mic & Speaker)
- Horizontal Rotation : 266°, Vertical Rotation: 90°
- Support 10x Digital Zoom
- 6 Preset Points for favorite location
- Smart Human Detection, Motion Detection, Smart Tracking
- Mobile Notification on Human & Motion Detection
- Support Micro SD Card up to 256GB & Cloud Storage(Optional)
- Compatible with all ONVIF Supported NVRs
- QR Code Scanning for Network Connection
- Monitoring : Mobile / PC Software, Web CMS (TrueCloud Plus)
- IP66 Waterproof Rating, 4000 Lightning Protection.
- Alexa Support



Wi-Fi Network



3MP Resolution



256GB SD Card



10X Digital Zoom



H.265 Compression



All Time Color



Smart Tracking



Cloud Recording



Location Presets

Technical Specifications

Product Code	T18135S
Image Sensor	1/3" CMOS Sensor
Resolutions	3MP (2304 x 1296)
Lens	M12 4MM Lens
IR LED	6 Array
IR Distance	30 Meters
White LED	6 White Array
White LED Distance	20 Meters
Video Compression Standard	H.264 / H.265
Video Streaming	Main Stream : 2304 x 1296@15 fps Sub Stream : 800 x 448@15fps
Audio Input/Output	Two-way audio, Built-in microphone and speakers
Audio Compression Standard	AAC / G.711A
Zoom	10x Digital
Light Mode	Full Color / Infrared / Intelligent
DNR	3D Digital Noise Reduction
Day & Night	IR-cut Auto ICR
Min Illumination	Color : 0.01 Lux, Black & White : 0.001 Lux
White Balance	Auto
WDR	D-WDR
Mirror / Flip	On / Off
Electronic Shutter	Auto
On Screen Display (OSD)	Date, Time, & Title

AI Features	Motion Detection, Human Detection, Smart Tracking.
Monitoring	Android, iOS, Windows, Web CMS (TrueCloud Plus)
Slots	Micro SD Card
Storage	Support Micro SD Card up to 256GB & Cloud Storage (Optional)
Wi-Fi Network	Wi-Fi Network (IEEE802.11b / g / n)
Wired Network	RJ45 × 1 (10M / 100M Adaptive Ethernet Port)
Protocol	ONVIF / RTSPS / RTSP / RTMPS / RTMP
Light Mode Indication	LED Blink : Not connected to Network, LED Continuous ON : Connected to Network
Button	Reset Button
Connectors	RJ45 LAN connector (100 Mbps) and DC Power Input
Power Input	DC: 12V/1A (DC 2.1mm Connector)
Power Consumption	≤ 5W
Thunder Prevention	Standard IEC61000-4-5
Working Temperature / Humidity	0-50° C RH Less than 95% (No Condensation)
Storage Temperature / Humidity	-20° C to 60° C / 20% to 90% RH
Housing Type	Plastic (IP66)
Dimension	191mm X132mm X 170mm (H x W x L)
Net Weight	550 Gms
Gross Weight	800 Gms

*** Note: Product specifications are subject to change without prior notice.**