

3MP Smart Wi-Fi Bullet All Time Color Camera



FEATURES

- 3MP (2304 x 1296) Resolution
- All Time Color Vision
- Full Duplex Audio Intercom (Built-in High Sensitivity Mic & Speaker)
- Support 10x Digital Zoom
- Smart Human Detection, Motion Detection
- Mobile Notification on Human & Motion Detection
- Support Micro SD Card upto 256GB & Cloud Storage(Optional)
- Compatible with all ONVIF Supported NVRs
- QR Code Scanning for Network Connection
- Monitoring: Mobile/PC (TrueCloud Plus)
- IP66 Waterproof Rating, 4000 Lightning Protection.
- Alexa Support



Wi-Fi Network



3MP Resolution



Two Way Audio Intercom



256GB SD Card



10X Digital Zoom



Human Detection



All Time Color



IP66 Rating



Cloud Recording

Technical Specifications

Product Code	T18238S
Image Sensor	1/3" CMOS Sensor
Resolutions	3MP (2304 x 1296)
Lens	M12 4MM Lens
IR LED	9 Array
IR Distance	30 Meters
White LED	9 White Array
White LED Distance	20 Meters
Video Compression Standard	H.264/H.265
Video Streaming	Main Stream : 2304x1296@15 fps Sub Stream : 800x448@15fps
Audio Input/Output	Two-way audio, built-in microphone and speakers
Audio Compression Standard	AAC / G.711A
Zoom	10x Digital
Light Mode	Full Color / Infrared / Intelligent
Day & Night	IR-cut Auto ICR
Min Illumination	Color : 0.01 Lux, Black & White : 0.001 Lux
DNR	3D Digital Noise Reduction
White Balance	Auto
WDR	D-WDR
Mirror/Flip	On / Off
Electronic Shutter	Auto
On-Screen Display (OSD)	Date, Time, & Title

AI Features	Motion Detection, Human Detection.
Monitoring	Android, iOS, Windows (TrueCloud Plus)
Storage	Support Micro SD Card up to 256GB & Cloud Storage(Optional)
Wi-Fi Network	Wi-Fi (IEEE802.11 b /g / n)
Wired Network	RJ45 × 1(10M/100M Adaptive Ethernet Port)
Protocol	ONVIF / RTSPS / RTSP / RTMPS / RTMP
Connectors	RJ45 LAN connector (100 Mbps) and DC Power Input
Slots	Micro SD Card
Button	Reset Button
Light Mode Indication	LED Blink : Not connected to Network, LED Continuous ON : Connected to Network
Power Input	DC : 12V/1A (DC 2.1mm Connector)
Power Consumption	≤ 6W
Working Temperature / Humidity	0-50° C RH Less than 95% (No Condensation)
Storage Temperature / Humidity	-20° C to 60° C / 20% to 90% RH
Housing Type	Plastic (IP66)
Dimension	141.4mm X 69.8mm X 159mm (H x W x L)
Net Weight	205 Gms
Gross Weight	413 Gms

*** Note: Product specifications are subject to change without prior notice.**