

# 3MP 4G Bullet All Time Color Camera



## FEATURES

- 3MP (2304 x 1296) Resolution
- All-Time-Color Vision
- Full Duplex Audio Intercom (Built-in High Sensitivity Mic & Speaker)
- Support 10x Digital Zoom
- Smart Human Detection, Motion Detection
- Mobile Notification on Human & Motion Detection
- Support Micro SD Card up to 256GB & Cloud Storage(Optional)
- Compatible with NVRs
- QR Code Scanning for Network Connection
- Monitoring : Mobile, Web CMS (TrueCloud Plus)
- IP66 Waterproof Rating, 4000 Lightning Protection.
- Alexa Support



4G SIM Support



3MP Resolution



Two Way Audio Intercom



256GB SD Card



10X Digital Zoom



Human Detection



All Time Color



IP66 Rating



Cloud Recording

## Technical Specifications

Product Code	T18292SF
Image Sensor	1/3" CMOS Sensor
Resolutions	3MP (2304 x 1296)
Lens	M12 4MM Lens
IR LED	4 LED
IR Distance	30 Meters
White LED	4 LED
White LED Distance	20 Meters
Video Compression Standard	H.264 / H.265
Video Streaming	Main Stream : 2304 x 1296 @15 fps Sub Stream : 800 x 448 @15fps
Audio Input / Output	Two way audio, Built in microphone and speakers
Audio Compression Standard	AAC / G.711A
Zoom	10x Digital
Light Mode	Full Color / Infrared / Smart
Day & Night	IR-cut Auto ICR
Min Illumination	Color : 0.01 Lux, Black & White : 0.001 Lux
DNR	3D Digital Noise Reduction
White Balance	Auto
WDR	D - WDR
Mirror / Flip	On / Off
Electronic Shutter	Auto

On Screen Display (OSD)	Date, Time, & Title
AI Features	Human Detection, Motion Detection, Tampering Detection.
Monitoring	Android, iOS, Web CMS (TrueCloud Plus)
Storage	Support Micro SD Card upto 256GB & Cloud Storage(Optional)
Wired Network	RJ45 × 1 (10M/100M Adaptive Ethernet Port)
4G Frequency Band	FDD - LTE : B1 / B3 / B5 / B8; TDD - LTE : B34 / B38 / B39 / B40 / B41
Protocol	RTSPS / RTSP/ RTMPS / RTMP
Connectors	RJ45 LAN connector (100 Mbps) and DC Power Input
Slots	4G SIM Card / Micro SD Card
Button	Reset Button
Light Mode Indication	LED Blink : Not connected to Network, LED Continue ON : Connected to Network
Power Input	DC : 12V/1A (DC 2.1mm Connector)
Power Consumption	≤ 6W
Working Temperature / Humidity	0-50° C RH Less than 95% (No Condensation)
Storage Temperature / Humidity	-20° C to 60° C / 20% to 90% RH
Housing Type	Plastic (IP66)
Dimension	105mm X 90mm X 170mm (H x W x L)
Net Weight	235 Gms
Gross Weight	443 Gms

**\* Note: Product specifications are subject to change without prior notice.**